(19) World Intellectual Property Organization

International Bureau



Rec'd PCT/PTO 06 JUL 2005

(43) International Publication Date 29 July 2004 (29.07.2004)

(10) International Publication Number WO 2004/062809 A1

(51) International Patent Classification7:

B03B 13/00

(21) International Application Number:

PCT/AU2003/001727

(22) International Filing Date:

24 December 2003 (24.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003900089

10 January 2003 (10.01.2003)

(71) Applicant (for all designated States except US): BM AL-LIANCE COAL OPERATIONS PTY LTD [AU/AU]: Central Queensland Office, Peak Downs Mine, Private Mail Bag, Moranbah, Queensland 4744 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VINCE, Andrew [AU/AU]; Lot 10 The Dome, Lynette Drive, Nindaroo, Mackay, Queensland 4740 (AU).

(74) Agent: GRIFFITH HACK; 509 St Kilda Road, Melbourne, Victoria 3004 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR PROCESSING PARTICULATE MATERIAL



(57) Abstract: A method and apparatus for processing particulate material such as coal, and also for measuring the efficiency of separation of the coal is disclosed. Particulate material is supplied to a separator such as a heavy medium device containing a dense medium (6). A parameter of the device (6) indicative of separation cut point is measured. The parameter may be density of the medium, flow rate of material or pressure of feed as well as medium to coal ratio. Measurements of these parameters are made over a time period and, from the measurements, an induced value indicative of separating efficiency is determined. The induced value provides a measure of separation efficiency and also provides a value which can be compared with a predetermined value so that an alarm can be generated if the value departs from the predetermined value by a predetermined amount.